

MODEL/  
STEAM OUTPUT  
(kg/h)



Heat output (kW)	8	16	32	48	67	80	107	120	160	200	240
Electrical power (kW)	8,7	16,7	32,7	48,7	67,7	80,7	107,7	120,7	160,7	200,7	240,7

The following services are incurred depending on the design.

Electrical power control voltage 230 VAC (option MX-CPA) (kW)	0,25										
Electrical power cooling unit (kW)	0,95					1,45					
Electrical power feed water heating (kW)	9 / 18					9 / 18 / 27 / 36					
Operating voltage	380-480 V · 50/60 Hz										



ELECTRIC STEAM GENERATOR

## THE PERFORMANCE CLASS

GENERATION E

[TECHNICAL DATASHEET]

WE'D BE HAPPY TO ASSIST YOU!



CERTUSS  
Dampfautomaten  
GmbH & Co. KG

Phone: +49 (0)2151 578-235  
E-mail: [verkauf@certuss.com](mailto:verkauf@certuss.com)  
[www.certuss-emx.com](http://www.certuss-emx.com)



MODEL/  
STEAM OUTPUT  
(kg/h)

- 10
- 20
- 40
- 60
- 80
- 100
- 130
- 160
- 200
- 260
- 320

Heat output (kW)	8	16	32	48	67	80	107	120	160	200	240
Water volume (l)	37 (NW=18,5)			45 (NW=28,9)				89 (NW=56,7)			
Measures (mm)											
Empty weight (kg)	400			550				850			
Operating weight (kg)	520			630				960			
Design pressure	4 bar / 0,4 MPa 6 bar / 0,6 MPa 10 bar / 1,0 MPa 12 bar / 1,2 MPa 16 bar / 1,6 MPa										
Working pressure min. / max.	3,0 / 3,65 bar · 0,3 / 0,365 MPa 3,5 / 5,5 bar · 0,35 / 0,55 MPa 3,5 / 9,1 bar · 0,35 / 0,91 MPa 3,5 / 11,0 bar · 0,35 / 1,1 MPa 3,5 / 14,5 bar · 0,35 / 1,45 MPa										

CATEGORY		
In accordance to DGRL2014/68/EU	4 bar	II
	6-16 bar	III
In accordance to BetrSichV	4 bar	II
	6-10 bar	III
	12-16 bar	III

MATERIAL	
Pressure vessel	P235GH / Stainless steel (AISI 304/AISI 316 Ti)
Feed water tank	Stainless steel (AISI 316 Ti)
Armatures	Brass / Stainless steel (AISI 316L/AISI 316 Ti)
Housing	S235JR / Stainless steel (AISI 304)

MODEL/  
STEAM OUTPUT  
(kg/h)

- 10
- 20
- 40
- 60
- 80
- 100
- 130
- 160
- 200
- 260
- 320

Steam outlet	1/2"	1"
Soft water connection	1/2"	
Safety valve	4-6 bar	1"
	10-12 bar	1"
	16 bar	1"
Blow down / desalination line	1/2"	
Overflow / drainage feed water tank	1"	
Condensate return	1"	
Vapor vent line	1"	

## VOLUME

Volume water level (V)	45,5 ltr.
------------------------	-----------