

VapaLite

Simplified Humidification for a Light Commercial Application



Humidification and Steam Generation Specialists

Vapac[®]

VapaLite

Simplified Humidification for a Light Commercial Application

Humidity is essential to a healthy environment and for maintaining the correct conditions for people, furniture and equipment. The VapaLite is designed to meet the particular requirements of small commercial premises and can be used alongside all heating systems to maintain the required humidity levels during winter.

Low Voltage Control Circuit

The VapaLite internal control circuit is operated at 24 volts AC.

On/Off Humidistat Control

The VapaLite can be operated On/Off using a wall or duct mounted humidistat or external DC controller 0.5 V, 0 - 10 V, 2 - 10 V, 1 - 18V, 0 - 20 V, 4 - 20 mA.

Steam Distribution

A steam distribution nozzle is included for installation into the

ductwork system together with 1.5 m of both steam hose (22 mm diameter) and condensate hose (6 mm diameter). Stainless steel, steam distribution pipes are also available with 'in-duct' lengths 200, 300 and 400 mm.

Room Distribution Unit (RDU)

Where a VapaLite is used for free discharge and without a ducted air distribution system, a Room Distribution Unit (RDU) is available.

The RDU is mounted directly on top of the VapaLite and replaces the steam hose and duct steam distribution pipes. A small fan within the RDU blows steam into the room.

Water and Drain

The VapaLite includes a built-in fill-cup that provides a 25 mm air-gap in the water feed-line to prevent back-feeding or contamination of the feed water supply. The fill-cup includes a safety overflow circuit.

Casing

The casing is manufactured from zinc pre-coated steel. The electrical section is fully enclosed. Access to the steam production area is via a lockable cover. The electrical section slides out for easy front access.

Features

- ✓ Two capacities: 2 Kg/hr and 4 Kg/hr of steam generation.
- ✓ Powerful VapaNet operating system.
- ✓ Easy to use.
- ✓ Ideal for light commercial applications.
- ✓ Drain pump.
- ✓ Disposable and cleanable cylinders manufactured from recyclable materials.

VapaLite Units

LMV2 & LMV4	
Height*:	500 mm
Width:	325 mm
Depth:	230 mm
Wet Weight:	16 Kg
RDU Height:	183 mm
RDU Weight:	3.6 Kg

*Drain trap underneath projects making overall height 565 mm.

Technical Data

Operating Limits	Water Supply	Water and Drain Connections
Ambient Air Temperature 1°C to 35°C	Conductivity: 80 to 1000µs Ph: 7.3 to 8.0	Supply Water: ¾" BSP Drain Outlet: 35mm OD
Water Temperature 1°C to 30°C	Supply Pressure: 0.3 to 8 bar Silica: 0	
Duct Pressure: 50 Pa	Hardness: 50 to 500 ppm	

The Vapac logo is an internationally registered trademark and its equipment is covered by international patents.

We reserve the right to change the design or specification of the equipment without prior notice.

Distributor:

Vapac®

Vapac Humidity Control Limited

Fircroft Way Tel: +44 (0)1732 863447
Edenbridge Fax: +44 (0)1732 865658
Kent TN8 6EZ www.eaton-williams.com

An Eaton-Williams Company

0410163 VLMV /9.08/2